

LWG-TPA series

Blickle WAVE synthetic castors with stem, colour silver grey, wheel with thermoplastic rubber tread



100–110 kg

-20 °C to +60 °C

Bracket: LWG series

- high-quality nylon 6, impact resistant
- encapsulated, double-sealed, grooved ball bearing in the swivel head
- zinc-plated blue-passivated steel top plate fitting (Cr6-free)
- colour silver grey RAL 7001
- modern, appealing design

Wheel: TPA series


- tread: high-quality thermoplastic rubber-elastomer (TPE), hardness 85 Shore A, colour grey, non-marking, oil containing
- wheel centre: high-quality polypropylene, impact resistant, colour silver grey RAL 7001

Other features:

- the load capacity reduces at ambient temperatures above +30 °C

Additional details:

- bracket series: page 88
- brakes: page 112–113
- wheel series: page 60
- bearing types: page 84–85



Swivel castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LWG-TPA 101G-P25	LWG-TPA 101G-FI-P25	100	32	100	plain bore	138	90 x 66	75 x 45 / 61 x 51	8.5	38
LWG-TPA 101KF-P25	LWG-TPA 101KF-FI-P25	100	32	100	ball bearing (C)	138	90 x 66	75 x 45 / 61 x 51	8.5	38
LWG-TPA 126G-P25	LWG-TPA 126G-FI-P25	125	32	110	plain bore	163	90 x 66	75 x 45 / 61 x 51	8.5	40
LWG-TPA 126KF-P25	LWG-TPA 126KF-FI-P25	125	32	110	ball bearing (C)	163	90 x 66	75 x 45 / 61 x 51	8.5	40

For corrosion-resistant versions of synthetic castors, see page 166

Versions / options



	plain bore version	electrically conductive version, non-marking, grey	with plate size 78x66 mm 61x50/50x42 mm	in special colour
Technical description page		50	106	
Product code suffix		LWGE-...-ELS	-P28	
Available for		all ball bearing versions*	upon request	upon request

* Load capacity of electrically conductive version reduced by 35%